

JP100S

100,000 lb Towing Capacity



Standard Features:

- Sit down model
- Power steering
- Heavy duty long life torque hubs
- Regenerative dynamic motor braking
- Redundant hydraulic service foot brake
- Automatic parking brake
- Controlled acceleration & deceleration foot operated throttle
- 2 - 10 Hp continuous duty drive motors coupled directly to brake/torque hub results in fewer moving parts
- Proportional drive with steering position sensor
- Suspension system
- Battery charge indicator with hourmeter
- 16 - 6 volt batteries
- Emergency safety cut off switch
- Hydraulic system filtration
- Covered storage compartments with rubberized coating on aluminum diamond deck cover
- Wheel tie down strap
- Nylon winch strap
- Nylon strut straps
- Sealed winch tension safety switch with no mechanical linkage

- Pintle hitch (rear)
- Fire extinguisher
- Headlights
- Rear facing lights
- Strobe light
- Side marker lights
- Horn
- Reduced tire wear
- Solid rubber tires
- Finish: Durable Powder Coat Tronair Blue

Optional Equipment:

- Fully automated, multi-tap battery charger (indicate required frequency)
JP-204-50 (50 Hz) or JP-204-60 (60 Hz)
- K-4925 - Forward/Reverse Steering
- Aircraft adapters
- Tire chains
- Battery watering system
- Custom colors and graphics

www.jetporter.com

1.800.426.6301

www.tronair.com

USA

Email: sales@tronair.com

Tel: 419-866-6301

Asia

Email: tronairasia@tronair.com

Tel: 662 2121463

Australia/New Zeland

Email: cjones@tronair.com

Tel: 61 2 4028 6981

China/Hong Kong/Macau/Taiwan

Email: nyao@tronair.com

Tel: 86 137 6450 1982

Europe

Email: jnunn@tronair.com

Tel: 44 (0) 11 332 0436


Middle East, Africa, CIS

Email: hkarvani@tronair.com

Tel: 44 (0) 11 332 0436

JP100S

100,000 lb Towing Capacity



| | | MODELS | JP100S |
|-------------|----------------------------|--|--------|
| PERFORMANCE | Towing Capacity | 100,000 lb (45,359 kg) | |
| | Cradle Capacity | 10,000 lb (4,536 kg) | |
| | Empty Speed | 6.5 mph (10.5 kph) | |
| | Full Load Speed | 3 mph (4.8 kph) | |
| POWER | Motor Horsepower | 20 HP | |
| | Motor Duty Cycle | Continuous | |
| | Battery Type | Sixteen - 6 volt deep cycle | |
| | Charge Time Full Discharge | 8 hour average | |
| DIMENSIONS | Length | 209.3 in (531.6 cm) | |
| | Width | 70 in (177.8 cm) | |
| | Height | 38.75 in (98.4 cm) | |
| | Weight with Battery | 6,900 lb (3,130 kg) | |
| | Weight without Battery | 5,000 lb (2,268 kg) | |
| | Ground Clearance | 5.4 in (13.7 cm) | |
| | Deck Height | 24.2 in (61.6 cm) | |
| | Cradle Depth | 25.9 in (65.9 cm) | |
| | Cradle Width | 40 in (101.6 cm) | |
| | Cradle Lift Height | 7 in (17.8 cm) | |
| CHASSIS | Steering Tires | 4.00 x 8 (16 in O.D.) | |
| | Drive Tires | 21 X 5 X 15 | |
| | Brakes | Regenerative dynamic motor braking and manual hydraulic foot brake | |
| | Parking Brake | Automatic activated/deactivated | |